

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010 Issue date: 6/6/2022 Revision date: 6/6/2024 Version: 1.1

1.1. Product identifier	
Product form Trade name Type of product Product code Product group	 Mixture Air Scents autofresh automatic spray refills - Jasmine & amber Air freshener SH443 Trade product
1.2. Relevant identified uses of the su	bstance or mixture and uses advised against
Jse of the substance/mixture	:
1.3. Supplier's details	
Manufacturer Shield Chemicals (Pty) Ltd 9 London Rd Apex P.O. Box 1939 1501 Benoni – Gauteng South Africa F (011) 421 7111 Contact: Jayson Clark	
1.4. Emergency telephone number	
Emergency number	: (011) 421 7111
Classification according to the United Nation Aerosol, Category 1 Serious eye damage/eye irritation, Category 2. Hazardous to the aquatic environment – Acute Full text of H-statements: see section 16	H222;H229 A H319
2.2. Label elements	
Labelling according to the United Nations C	аналананананананананананананананананана
Hazard pictograms (GHS ZA)	
Signal word (GHS-ZA) Hazardous ingredients Hazard statements (GHS ZA)	 Danger Ethanol, propane, butane, liquefied, under pressure H222 - Extremely flammable aerosol. H229 - Pressurised container: May burst if heated. H319 - Causes serious eye irritation.
	H401 - Toxic to aquatic life

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

	P280 - Wear eye protection, protective clothing, protective gloves. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 - Dispose of contents and container to an approved waste disposal plant.
2.3. Other hazards	
Adverse physicochemical, human health and environmental effects	: Pressurised container: May burst if heated, Extremely flammable aerosol, Causes serious eye irritation, Toxic to aquatic life

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
butane, liquefied, under pressure	CAS-No.: 106-97-8	40.0 - 50.0	Pyr. Gas Not classified Flam. Gas 1, H220 Aquatic Acute 2, H401
Ethanol	CAS-No.: 64-17-5	20.0 - 30.0	Flam. Liq. 2, H225 Acute Tox. Not classified (Oral) Acute Tox. Not classified (Dermal) Acute Tox. Not classified (Inhalation:dust,mist) Eye Irrit. 2A, H319 Aquatic Acute Not classified
propane	CAS-No.: 74-98-6	20.0 - 30.0	Pyr. Gas Not classified Flam. Gas 1, H220 Aquatic Acute Not classified

SECTION 4: First aid measures	
4.1. Description of first aid measures	3
First-aid measures after inhalation First-aid measures after skin contact First-aid measures after eye contact	 Remove person to fresh air and keep comfortable for breathing. Wash skin with plenty of water. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion 4.2. Most important symptoms and e	: Call a poison center or a doctor if you feel unwell.
Symptoms/effects after eye contact	: Eye irritation.
4.3. Indication of any immediate med	lical attention and special treatment needed
Tract symptometically	

Treat symptomatically.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

5.2. Special hazards arising from the substa	. Special hazards arising from the substance or mixture	
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	 Extremely flammable aerosol. Pressurised container: May burst if heated. Toxic fumes may be released. 	
5.3. Advice for firefighters		
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.	

SECTION 6: Accidental release measures	
6.1. Personal precautions, protective equip	oment and emergency procedures
No additional information available	
6.1.1. For non-emergency personnel	
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	
Avoid release to the environment.	
6.3. Methods and material for containment	and cleaning up
For containment Methods for cleaning up Other information	 Collect spillage. Mechanically recover the product. Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Precautions for safe handling Hygiene measures	 Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin and eyes. Wear personal protective equipment. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. 	
7.2. Conditions for safe storage, inc	cluding any incompatibilities	
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a	

well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

propane (74-98-6)	
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Propane
OEL TWA	1800 mg/m³
OEL TWA [ppm]	1000 ppm

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

propane (74-98-6)		
Regulatory reference	Government Notice No. R 904	
butane, liquefied, under pressure (106-97-8)		
South Africa - Occupational Exposure Limits (Reco	mmended Limits)	
Local name	Butane	
OEL TWA	1430 mg/m ³	
OEL TWA [ppm]	600 ppm	
OEL STEL	1780 mg/m ³	
OEL STEL [ppm]	750 ppm	
Regulatory reference	Government Notice. R: 1179	
South Africa - Occupational Exposure Limits (Airborne Pollutants)		
Local name	n-Butane	
OEL TWA	1430 mg/m ³	
OEL TWA [ppm]	600 ppm	
OEL STEL	1780 mg/m ³	
OEL STEL [ppm]	750 ppm	
Regulatory reference	Government Notice No. R 904	
8.2. Appropriate engineering controls		
Appropriate engineering controls :	Ensure good ventilation of the work station.	

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection	Protective gloves
Eye protection	Safety glasses
Skin and body protection	Wear suitable protective clothing
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties 9.1. Information on basic physical and chemical properties	
Appearance	: Liquid.
Colour	: clear.
Odour	: jasmine-like.
Odour threshold	: No data available
DH	: 8 – 10.5
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available

Melting point

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: No data available
Vapour pressure at 50 °C	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Relative density of saturated gas/air mixture	: No data available
Density	: No data available
Relative gas density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Oxidising properties	: No data available
Explosive limits	: No data available
Lower explosive limit (LEL)	: No data available
Upper explosive limit (UEL)	: No data available

9.2. (

 No data available Pressurised container: May burst if heated. No data available
er: May burst if heated.

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information		
11.1. Information on toxicologica	al effects	
Acute toxicity (oral) Acute toxicity (dermal) Acute toxicity (inhalation)	: Not classified : Not classified : Not classified	
Ethanol (64-17-5)		
LD50 oral rat	10470 mg/kg	

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

Ethanol (64-17-5)		
LD50 dermal rabbit		> 15800 mg/kg
LC50 Inhalation - Rat		51 mg/l/4h
propane (74-98-6)		
LC50 Inhalation - Rat [ppm] > 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (g		> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))
butane, liquefied, under pressure (106-97-8)	
LC50 Inhalation - Rat		1442.738 – 1443 mg/l 15 MIN
LC50 Inhalation - Rat [ppm]		800000 ppm 15 MIN
Skin corrosion/irritation		Not classified bH: 8 – 10.5
Serious eye damage/irritation		Causes serious eye irritation. bH: 8 – 10.5
Respiratory or skin sensitisation	: N	Not classified
Germ cell mutagenicity	: N	Not classified
Carcinogenicity	: N	Not classified
Reproductive toxicity	: N	Not classified
STOT-single exposure	: N	Not classified
STOT-repeated exposure	: N	Not classified
Aspiration hazard	: N	Not classified
Air Scents autofresh automatic spr	ay refills - J	lasmine & amber
Vaporizer		Aerosol

SECTION 12: Ecological information	
12.1. Toxicity	
Hazardous to the aquatic environment, short-term : (acute)	Toxic to aquatic life. Toxic to aquatic life. Not classified
Ethanol (64-17-5)	
LC50 - Fish [1]	11.2 mg/l
EC50 - Crustacea [1]	5012 mg/l
Bioconcentration factor (BCF REACH)	< 10
propane (74-98-6)	
LC50 - Fish [1]	24 mg/l (96 h, Pisces, Literature study)
LC50 - Fish [2]	49.9 mg/l (96 h, Pisces, Fresh water, QSAR)
EC50 - Crustacea [1]	7 mg/l (48 h, Daphnia magna, Literature study)
BCF - Fish [1]	9 – 25 (Pisces, QSAR)
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)
butane, liquefied, under pressure (106-97-8)	
LC50 - Fish [1]	> 1000 mg/l (96 h, Pimephales promelas, QSAR)
EC50 72h - Algae [1]	5.3 – 5.5 mg/l (Algae, QSAR)
Partition coefficient n-octanol/water (Log Pow)	2.89 (Experimental value)

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

12.2. Persistence and degradability	
Air Scents autofresh automatic spray refills -	Jasmine & amber
Persistence and degradability	No additional information available
Ethanol (64-17-5)	
Chemical oxygen demand (COD)	2.04 g O ₂ /g substance
propane (74-98-6)	
Persistence and degradability	Readily biodegradable in water.
butane, liquefied, under pressure (106-97-8)	
Persistence and degradability	Readily biodegradable in water.
12.3. Bioaccumulative potential	
Air Scents autofresh automatic spray refills -	Jasmine & amber
Bioaccumulative potential	No additional information available
Ethanol (64-17-5)	
Bioconcentration factor (BCF REACH)	< 10
propane (74-98-6)	·
BCF - Fish [1]	9 – 25 (Pisces, QSAR)
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
butane, liquefied, under pressure (106-97-8)	
Partition coefficient n-octanol/water (Log Pow)	2.89 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
12.4. Mobility in soil	
Air Scents autofresh automatic spray refills -	Jasmine & amber
Mobility in soil	No additional information available
Ethanol (64-17-5)	
Mobility in soil	1
propane (74-98-6)	
Surface tension	0.016 N/m (-47 °C)
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)
Ecology - soil	Not applicable (gas).
butane, liquefied, under pressure (106-97-8)	-
Surface tension	< 0.1 N/m (0 °C)
Partition coefficient n-octanol/water (Log Pow)	2.89 (Experimental value)
Ecology - soil	Not applicable (gas).
12.5. Other adverse effects	
	Not classified
Other adverse effects :	No additional information available

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods

: Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with SANS / IMDG / IATA		
SANS	IMDG	ΙΑΤΑ
14.1. UN number		•
1950	1950	1950
14.2. Proper Shipping Name		•
AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)		•
2.1	2.1	2.1
14.4. Packing group		•
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		1
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available		•
14.6. Special precautions for user		
SANS Special provisions (SANS) Limited quantities (SANS) Limited quantities (SANS) Packagings, large packagings and IBCs Packing instructions (SANS) Packagings, large packagings and IBCs Special packing instructions (SANS)	 : 63, 190 : See SP277 : See SP277 : P003 : PP17, PP87 	
IMDG Special provisions (IMDG) Packing instructions (IMDG) Special packing provisions (IMDG) EmS-No. (Fire) EmS-No. (Spillage) Stowage category (IMDG)	 63, 190, 277, 327, 344, 381, 959 P207, LP200 PP87, L2 F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE) None 	
IATA PCA Excepted quantities (IATA) PCA Limited quantities (IATA) PCA limited quantity max net quantity (IATA) PCA packing instructions (IATA) PCA max net quantity (IATA) CAO packing instructions (IATA)	: E0 : Y203 : 30kgG : 203 : 75kg : 203	

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

ERG code (IATA)

: 10L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health, and environmental national regulations specific for the product

No additional information available

SECTION 16: Other informat	ion	
Issue date	: 06/06/2022	
Revision date	: 06/06/2024	

Full text of	f H-statements
H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H227	Combustible liquid
H302	Harmful if swallowed.
H303	May be harmful if swallowed
H311	Toxic in contact with skin.
H313	May be harmful in contact with skin
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Safety Data Sheet (SDS), South Africa

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.