

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010
Issue date: 1/25/2024 Revision date: 11/9/2025 Supersedes: 1/25/2026 Version: 1.1

## **SECTION 1: Identification**

### 1.1. Product identifier

Product form : Mixture

Trade name : Air Scents air enhancer extra value - forest green

Type of product : Air freshener Product code : SH1497 Product group : Trade product

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

### 1.3. Supplier's details

#### Manufacturer

Shield Chemicals (Pty) Ltd 9 London Rd Apex P.O. Box 1939 1501 Benoni - Gauteng South Africa T (011) 421 7111 Contact: Jayson Clark

### 1.4. Emergency telephone number

Emergency number : (011) 421 7111

# **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Classification according to the United Nations GHS

Flammable liquids Not classified Carcinogenicity Not classified

Full text of H-statements: see section 16

### 2.2. Label elements

#### Labelling according to the United Nations GHS

No labelling applicable

### 2.3. Other hazards

Adverse physicochemical, human health and

: May cause an allergic skin reaction, Harmful to aquatic life

environmental effects

### **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

Not applicable

### Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
butane, liquefied, under pressure	CAS-No.: 106-97-8	30.555	Flam. Gas 1, H220 Pyr. Gas Not classified Press. Gas (Liq.), H280 Acute Tox. Not classified (Inhalation:gas)
Ethanol	CAS-No.: 64-17-5	5.7	Flam. Liq. 1, H224 Acute Tox. Not classified (Oral) STOT RE Not classified Aquatic Acute Not classified
propane	CAS-No.: 74-98-6	1.05	Flam. Gas 1, H220 Pyr. Gas Not classified Press. Gas (Liq.), H280 Acute Tox. Not classified (Inhalation:gas) Aquatic Acute Not classified

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash

occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : May cause an allergic skin reaction.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing vapours.

11/9/2025 (Revision date) ZA - en 2/9

### Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Avoid

breathing vapours. Wear personal protective equipment.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash

contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

Ethanol (64-17-5)		
South Africa - Occupational Exposure Limits (Airborne Pollutants)		
Local name	Ethanol (Ethyl alcohol)	
OEL TWA	1900 mg/m³	
OEL TWA	1000 ppm	
Regulatory reference	Government Notice No. R 904	
butane, liquefied, under pressure (106-97-8)		
South Africa - Occupational Exposure Limits (Airbo	orne Pollutants)	
Local name	n-Butane	
OEL TWA	1430 mg/m³	
OEL TWA	600 ppm	
OEL STEL	1780 mg/m³	
OEL STEL	750 ppm	
Regulatory reference	Government Notice No. R 904	
propane (74-98-6)		
South Africa - Occupational Exposure Limits (Airborne Pollutants)		
Local name	Propane	
OEL TWA	1800 mg/m³	
OEL TWA	1000 ppm	
Regulatory reference	Government Notice No. R 904	

11/9/2025 (Revision date) ZA - en 3/9

### Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Protective gloves
Eye protection : Safety glasses

Skin and body protection : Wear suitable protective clothing

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

### Personal protective equipment symbol(s):







### 8.4. Exposure limit values for the other components

No additional information available

# SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state: LiquidAppearance: Liquid.Colour: White.Odour: characteristic.Odour threshold: No data available

pH : 6.5 – 8

pH solution : No data available
Relative evaporation rate (butylacetate=1) : No data available
Relative evaporation rate (ether=1) : No data available
Melting point : Not applicable
Freezing point : No data available
Boiling point : No data available

Flash point : > 100 °C

Auto-ignition temperature : No data available Decomposition temperature : No data available Flammability : Not applicable Vapour pressure : No data available : No data available Vapour pressure at 50°C : No data available Relative vapour density at 20°C : No data available Relative density Relative density of saturated gas/air mixture : No data available Density No data available Relative gas density No data available No data available Solubility No data available Partition coefficient n-octanol/water (Log Pow) Partition coefficient n-octanol/water (Log Kow) No data available Viscosity, kinematic No data available Viscosity, dynamic No data available Explosive properties No data available Oxidising properties No data available No data available **Explosive limits** Lower explosion limit : No data available

#### 9.2. Other information

Upper explosion limit

No additional information available

No data available

### Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### **SECTION 11: Toxicological information**

1	1 1	Informatio	n on toxico	logical	effects
		ппоппацо	II OII LUXILU	louicai	enecis

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acute toxicity (illinatation)	. Not classified
Ethanol (64-17-5)	
LD50 oral rat	10470 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 9720 - 11380
butane, liquefied, under pressure (	106-97-8)
LC50 Inhalation - Rat	1442.738 – 1443 mg/l 15 MIN
LC50 Inhalation - Rat [ppm]	800000 ppm 15 MIN
propane (74-98-6)	
LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))
Skin corrosion/irritation	: Not classified pH: 6.5 – 8
Serious eye damage/irritation	: Not classified pH: 6.5 – 8
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Ethanol (64-17-5)	
LOAEL (oral, rat, 90 days)	3200 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

Aspiration hazard : Not classified

NOAEL (oral, rat, 90 days)

1730 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Remarks on results: other:

# Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

Air Scents air enhancer extra value - forest green		
Vaporizer	Spray	
Ethanol (64-17-5)		
Animal studies and expert judgment for classification	False	
butane, liquefied, under pressure (106-97-8)		
Animal studies and expert judgment for classification	False	
propane (74-98-6)		
Animal studies and expert judgment for classification	False	

# SECTION 12: Ecological information

## 12.1. Toxicity

Ecology - general : Harmful to aquatic life.

Hazardous to the aquatic environment, short-term

(acute)

: Not classified

Hazardous to the aquatic environment, long-term : Not classified

(chronic)

(0.1101110)	
Ethanol (64-17-5)	
EC50 - Crustacea [1]	> 10000 mg/l Test organisms (species): Daphnia magna
butane, liquefied, under pressure (106-97-	8)
LC50 - Fish [1]	1000 mg/l (96 h, Pimephales promelas, QSAR)
EC50 72h - Algae [1]	5.3 – 5.5 mg/l (Algae, QSAR)
Partition coefficient n-octanol/water (Log Pow)	2.89 (Experimental value)
propane (74-98-6)	
LC50 - Fish [1]	24 mg/l (96 h, Pisces, Literature study)
LC50 - Fish [2]	49.9 mg/l (96 h, Pisces, Fresh water, QSAR)
EC50 - Crustacea [1]	7 mg/l (48 h, Daphnia magna, Literature study)
BCF - Fish [1]	9 – 25 (Pisces, QSAR)
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)

### 12.2. Persistence and degradability

Air Scents air enhancer extra value - forest green		
Persistence and degradability	No additional information available	
butane, liquefied, under pressure (106-97-8)		
Persistence and degradability	Readily biodegradable in water.	
propane (74-98-6)		
Persistence and degradability	Readily biodegradable in water.	

# 12.3. Bioaccumulative potential

Air Scents air enhancer extra value - forest green	
Bioaccumulative potential	No additional information available

# Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

butane, liquefied, under pressure (106-97-8)		
Partition coefficient n-octanol/water (Log Pow)	2.89 (Experimental value)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
propane (74-98-6)		
BCF - Fish [1]	9 – 25 (Pisces, QSAR)	
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	

## 12.4. Mobility in soil

Air Scents air enhancer extra value - forest green		
Mobility in soil	No additional information available	
butane, liquefied, under pressure (106-97-8)		
Surface tension	< 0.1 N/m (0 °C)	
Partition coefficient n-octanol/water (Log Pow)	2.89 (Experimental value)	
Ecology - soil	Not applicable (gas).	
propane (74-98-6)		
Surface tension	0.016 N/m (-47 °C)	
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)	
Ecology - soil	Not applicable (gas).	

# 12.5. Other adverse effects

Ozone : Not classified

Other adverse effects : No additional information available

## **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## **SECTION 14: Transport information**

In accordance with SANS / IMDG / IATA

SANS	IMDG	IATA	
14.1. UN number	14.1. UN number		
Not regulated for transport			
14.2. Proper Shipping Name			
Not applicable	Not applicable	Not applicable	
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	
Not applicable	Not applicable	Not applicable	
14.4. Packing group			
Not applicable	Not applicable	Not applicable	

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

SANS	IMDG	IATA	
14.5. Environmental hazards			
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	
No supplementary information available			

### 14.6. Special precautions for user

#### **SANS**

No data available

#### **IMDG**

No data available

#### **IATA**

No data available

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

# **SECTION 15: Regulatory information**

### 15.1. Safety, health, and environmental national regulations specific for the product

No additional information available

### **SECTION 16: Other information**

 Issue date
 : 25/01/2024

 Revision date
 : 09/11/2025

 Supersedes
 : 25/01/2026

Full text of H-statements	
H220	Extremely flammable gas
H224	Extremely flammable liquid and vapour
H226	Flammable liquid and vapour
H227	Combustible liquid
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H303	May be harmful if swallowed
H313	May be harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H361	Suspected of damaging fertility or the unborn child
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life

# Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

Full text of H-statements	
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), South Africa

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.