

# Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010 Issue date: 5/24/2024 Revision date: 5/24/2026 Version: 1.1

#### **SECTION 1: Identification**

#### 1.1. Product identifier

Product form : Mixture

Trade name : Air Scents autofresh automatic spray refills - Jasmine & amber

Type of product : Air freshener
Product code : SH443
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture :

#### 1.3. Supplier's details

#### Manufacturer

Shield Chemicals (Pty) Ltd 9 London Rd Apex P.O. Box 1939 1501 Benoni – Gauteng South Africa T (011) 421 7111

Contact: Jayson Clark

#### 1.4. Emergency telephone number

Emergency number : (011) 421 7111

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

# **Classification according to the United Nations GHS**

Aerosol, Category 1 H222;H229
Serious eye damage/eye irritation, Category 2A H319
Full text of H-statements: see section 16

#### 2.2. Label elements

#### **Labelling according to the United Nations GHS**

Hazard pictograms (GHS ZA) :





Signal word (GHS-ZA) : Danger

Hazard statements (GHS ZA) : H222 - Extremely flammable aerosol

H229 - Pressurised container: May burst if heated

H319 - Causes serious eye irritation

Precautionary statements (GHS ZA) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P280 - Wear eye protection, protective clothing, protective gloves.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

### Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

#### 2.3. Other hazards

Adverse physicochemical, human health and environmental effects

: Pressurised container: May burst if heated, Extremely flammable aerosol, Causes serious eye irritation, Toxic to aquatic life

### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
butane, liquefied, under pressure	CAS-No.: 106-97-8	40.0 - 50.0	Flam. Gas 1, H220 Pyr. Gas Not classified Press. Gas (Liq.), H280 Acute Tox. Not classified (Inhalation:gas)
Ethanol	CAS-No.: 64-17-5	20.0 - 30.0	Flam. Liq. 2, H225 Acute Tox. Not classified (Oral) Acute Tox. Not classified (Dermal) Acute Tox. Not classified (Inhalation:dust,mist) Eye Irrit. 2A, H319 Aquatic Acute Not classified
propane	CAS-No.: 74-98-6	20.0 - 30.0	Flam. Gas 1, H220 Pyr. Gas Not classified Press. Gas (Liq.), H280 Acute Tox. Not classified (Inhalation:gas) Aquatic Acute Not classified

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after eye contact : Eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5/24/2026 (Revision date) ZA - en 2/9

#### Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

#### 5.3. Advice for firefighters

Protection during firefighting

: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

#### 6.1.1. For non-emergency personnel

**Emergency procedures** 

: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling

: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures

: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

Local name

: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

propane (74-98-6)		
South Africa - Occupational Exposure Limits (Airborne Pollutants)		
Local name	Propane	
OEL TWA	1800 mg/m³	
OEL TWA	1000 ppm	
Regulatory reference	Government Notice No. R 904	
butane, liquefied, under pressure (106-97-8)		
South Africa - Occupational Exposure Limits (Airborne Pollutants)		

5/24/2026 (Revision date) ZA - en 3/9

n-Butane

### Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

butane, liquefied, under pressure (106-97-8)	
OEL TWA	1430 mg/m³
OEL TWA	600 ppm
OEL STEL	1780 mg/m³
OEL STEL	750 ppm
Regulatory reference	Government Notice No. R 904

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Environmental exposure controls : Avoid release to the environment.

#### 8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Protective gloves
Eye protection : Safety glasses

Skin and body protection : Wear suitable protective clothing

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

#### Personal protective equipment symbol(s):







#### 8.4. Exposure limit values for the other components

No additional information available

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.
Colour : clear.
Odour : jasmine-like.
Odour threshold : No data available

pH : 8 – 10.5

pH solution No data available Relative evaporation rate (butylacetate=1) No data available Relative evaporation rate (ether=1) No data available Melting point Not applicable Freezing point No data available **Boiling point** No data available Flash point No data available Auto-ignition temperature No data available Decomposition temperature No data available

Flammability : Extremely flammable aerosol.

Vapour pressure : No data available
Vapour pressure at 50°C : No data available
Relative vapour density at 20°C : No data available
Relative density : No data available
Relative density of saturated gas/air mixture : No data available
Density : No data available
Relative gas density : No data available
Solubility : No data available

Solubility : No data available
Partition coefficient n-octanol/water (Log Pow) : No data available
Partition coefficient n-octanol/water (Log Kow) : No data available
Viscosity, kinematic : No data available

### Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

Viscosity, dynamic : No data available

Explosive properties : Pressurised container: May burst if heated.

Oxidising properties : No data available Explosive limits : No data available Lower explosion limit : No data available Upper explosion limit : No data available : No data available

#### 9.2. Other information

No additional information available

### **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Ethanol (64-17-5)		
LD50 oral rat	10470 mg/kg	
LD50 dermal rabbit	> 15800 mg/kg	
LC50 Inhalation - Rat	51 mg/l/4h	
propane (74-98-6)		
LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))	
butane, liquefied, under pressure (106-97-8)		
LC50 Inhalation - Rat	1442.738 – 1443 mg/l 15 MIN	
LC50 Inhalation - Rat [ppm]	800000 ppm 15 MIN	
Skin corrosion/irritation	: Not classified	

Skin corrosion/irritation : Not classified pH: 8 – 10.5

Serious eye damage/irritation : Causes serious eye irritation.

pH: 8 – 10.5

Respiratory or skin sensitisation : Not classified Germ cell mutagenicity : Not classified

# Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

•		
Air Scents autofresh automatic spray refills - Jasmine & amber		
Vaporizer	Aerosol	
Ethanol (64-17-5)		
Animal studies and expert judgment for classification	False	
propane (74-98-6)		
Animal studies and expert judgment for classification	False	
butane, liquefied, under pressure (106-97-8)		
Animal studies and expert judgment for classification	False	

# **SECTION 12: Ecological information**

# 12.1. Toxicity

Ecology - general : Toxic to aquatic life. Hazardous to the aquatic environment, short–term : Not classified

(acute)

Hazardous to the aquatic environment, long-term : Not classified

(chronic)

Ethanol (64-17-5)		
11.2 mg/l		
5012 mg/l		
< 10		
propane (74-98-6)		
24 mg/l (96 h, Pisces, Literature study)		
49.9 mg/l (96 h, Pisces, Fresh water, QSAR)		
7 mg/l (48 h, Daphnia magna, Literature study)		
9 – 25 (Pisces, QSAR)		
1.09 – 2.8 (Experimental value, 20 °C)		
butane, liquefied, under pressure (106-97-8)		
1000 mg/l (96 h, Pimephales promelas, QSAR)		
5.3 – 5.5 mg/l (Algae, QSAR)		
2.89 (Experimental value)		

# 12.2. Persistence and degradability

Air Scents autofresh automatic spray refills - Jasmine & amber		
Persistence and degradability	No additional information available	
Ethanol (64-17-5)		
Chemical oxygen demand (COD)	2.04 g O <sub>2</sub> /g substance	
propane (74-98-6)		
Persistence and degradability	Readily biodegradable in water.	

# Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

butane, liquefied, under pressure (106-97-8)	
Persistence and degradability	Readily biodegradable in water.

# 12.3. Bioaccumulative potential

Air Scents autofresh automatic spray refills - Jasmine & amber		
Bioaccumulative potential	No additional information available	
Ethanol (64-17-5)		
Bioconcentration factor (BCF REACH)	< 10	
propane (74-98-6)		
BCF - Fish [1]	9 – 25 (Pisces, QSAR)	
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
butane, liquefied, under pressure (106-97-8)		
Partition coefficient n-octanol/water (Log Pow)	2.89 (Experimental value)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	

# 12.4. Mobility in soil

Air Scents autofresh automatic spray refills - Jasmine & amber		
Mobility in soil	No additional information available	
Ethanol (64-17-5)		
Mobility in soil	1	
propane (74-98-6)		
Surface tension	0.016 N/m (-47 °C)	
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)	
Ecology - soil	Not applicable (gas).	
butane, liquefied, under pressure (106-97-8)		
Surface tension	< 0.1 N/m (0 °C)	
Partition coefficient n-octanol/water (Log Pow)	2.89 (Experimental value)	
Ecology - soil	Not applicable (gas).	

### 12.5. Other adverse effects

Ozone : Not classified

Other adverse effects : No additional information available

# **SECTION 13: Disposal considerations**

# 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

# **SECTION 14: Transport information**

In accordance with SANS / IMDG / IATA

# Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

SANS	IMDG	IATA
14.1. UN number		
1950	1950	1950
14.2. Proper Shipping Name		
AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)		
2.1	2.1	2.1
3	2	2
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available		

#### 14.6. Special precautions for user

#### SANS

Special provisions (SANS) : 63, 190
Limited quantities (SANS) : See SP277
Limited quantities (SANS) : See SP277
Packagings, large packagings and IBCs Packing : P003

instructions (SANS)

Packagings, large packagings and IBCs Special

packing instructions (SANS)

: PP17, PP87

# IMDG

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Packing instructions (IMDG) : P207, LP200 Special packing provisions (IMDG) : PP87, L2

EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES

EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)

Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

#### IATA

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

# Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

# **SECTION 15: Regulatory information**

#### 15.1. Safety, health, and environmental national regulations specific for the product

No additional information available

# **SECTION 16: Other information**

 Issue date
 : 24/05/2024

 Revision date
 : 24/05/2026

Full text of H-statements	
H220	Extremely flammable gas
H225	Highly flammable liquid and vapour
H227	Combustible liquid
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H303	May be harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H313	May be harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), South Africa

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.