

#### Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010 Issue date: 5/28/2024 Revision date: 5/28/2026 Version: 1.1

# **SECTION 1: Identification**

#### 1.1. Product identifier

Product form : Mixture

Trade name : Air Scents fresh dry room spray - Amber & oud

Type of product : Air freshener
Product code : SH1290
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture :

#### 1.3. Supplier's details

#### Manufacturer

Shield Chemicals (Pty) Ltd 9 London Rd Apex P.O. Box 1939 1501 Benoni – Gauteng South Africa T (011) 421 7111 Contact: Jayson Clark

#### 1.4. Emergency telephone number

Emergency number : (011) 421 7111

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### **Classification according to the United Nations GHS**

Aerosol, Category 1 H222;H229
Serious eye damage/eye irritation, Category 2A H319
Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412

Full text of H-statements: see section 16

#### 2.2. Label elements

#### Labelling according to the United Nations GHS

Hazard pictograms (GHS ZA) :





Signal word (GHS-ZA) : Danger

Hazardous ingredients : 1-(1,2,3,4,5,6,7,8-octahydro-2,3,8,8-tetramethyl-2-naphthyl)ethan-1-one

Hazard statements (GHS ZA) : H222 - Extremely flammable aerosol

H229 - Pressurised container: May burst if heated H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation

H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (GHS ZA) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P261 - Avoid breathing spray.

P272 - Contaminated work clothing should not be allowed out of the workplace.

#### Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

P273 - Avoid release to the environment.

P280 - Wear eye protection, protective clothing, protective gloves.

P302+P352 - IF ON SKIN: Wash with plenty of soap and water

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 - Specific treatment (see ... on this label).

P333+P317 - If skin irritation or rash occurs: Get medical help.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501 - Dispose of contents and container to a hazardous or special waste collection point.

#### 2.3. Other hazards

Adverse physicochemical, human health and environmental effects

: Pressurised container: May burst if heated, Extremely flammable aerosol, May cause an allergic skin reaction, Causes serious eye irritation, Toxic to aquatic life, Harmful to aquatic life with long lasting effects.

# **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
butane, liquefied, under pressure	CAS-No.: 106-97-8	40.0 - 50.0	Flam. Gas 1, H220 Pyr. Gas Not classified Press. Gas (Liq.), H280 Acute Tox. Not classified (Inhalation:gas)
Ethanol	CAS-No.: 64-17-5	30.0 - 40.0	Flam. Liq. 2, H225 Acute Tox. Not classified (Oral) Acute Tox. Not classified (Dermal) Acute Tox. Not classified (Inhalation:dust,mist) Eye Irrit. 2A, H319 Aquatic Acute Not classified
diethyl phthalate	CAS-No.: 84-66-2	1.0 - 5.0	Flam. Liq. Not classified STOT RE Not classified Aquatic Acute 3, H402 Aquatic Chronic Not classified
propane	CAS-No.: 74-98-6	20.0 - 30.0	Flam. Gas 1, H220 Pyr. Gas Not classified Press. Gas (Liq.), H280 Acute Tox. Not classified (Inhalation:gas) Aquatic Acute Not classified

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures after inhalation First-aid measures after skin contact

- : Remove person to fresh air and keep comfortable for breathing.
- : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact

: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion

: Call a poison center or a doctor if you feel unwell.

5/28/2026 (Revision date) ZA - en 2/10

#### Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin

and eyes. Avoid breathing spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin and

eyes. Avoid breathing spray. Wear personal protective equipment.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash

contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

#### Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a

well-ventilated place. Keep cool.

#### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

propane (74-98-6)	propane (74-98-6)					
South Africa - Occupational Exposure Limits (Airbo	South Africa - Occupational Exposure Limits (Airborne Pollutants)					
Local name	Propane					
OEL TWA	1800 mg/m³					
OEL TWA	1000 ppm					
Regulatory reference	Government Notice No. R 904					
butane, liquefied, under pressure (106-97-8)	butane, liquefied, under pressure (106-97-8)					
South Africa - Occupational Exposure Limits (Airborne Pollutants)						
Local name	n-Butane					
OEL TWA	1430 mg/m³					
OEL TWA	600 ppm					
OEL STEL	1780 mg/m³					
OEL STEL	750 ppm					
Regulatory reference	Government Notice No. R 904					
diethyl phthalate (84-66-2)						
South Africa - Occupational Exposure Limits (Airbo	South Africa - Occupational Exposure Limits (Airborne Pollutants)					
Local name	Diethyl phthalate					
OEL TWA	5 mg/m³					

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Environmental exposure controls : Avoid release to the environment.

#### 8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Protective gloves
Eye protection : Safety glasses

Skin and body protection : Wear suitable protective clothing

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

10 mg/m<sup>3</sup>

Government Notice No. R 904

#### Personal protective equipment symbol(s):



OEL STEL

Regulatory reference





#### 8.4. Exposure limit values for the other components

No additional information available

5/28/2026 (Revision date) ZA - en 4/10

#### Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: LiquidAppearance: Liquid.Colour: clear.

Odour Amber & oud. No data available Odour threshold No data available No data available pH solution Relative evaporation rate (butylacetate=1) : No data available Relative evaporation rate (ether=1) : No data available Melting point : Not applicable Freezing point : No data available Boiling point : No data available Flash point : No data available : No data available Auto-ignition temperature : No data available Decomposition temperature

Flammability : Extremely flammable aerosol.

Vapour pressure : No data available Vapour pressure at 50°C : No data available Relative vapour density at 20°C : No data available Relative density : No data available Relative density of saturated gas/air mixture : No data available : No data available Density Relative gas density : No data available Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available Partition coefficient n-octanol/water (Log Kow) : No data available

Viscosity, dynamic : No data available Explosive properties : Pressurised container: May burst if heated.

: No data available

Oxidising properties : No data available
Explosive limits : No data available
Lower explosion limit : No data available
Upper explosion limit : No data available

#### 9.2. Other information

Viscosity, kinematic

No additional information available

#### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

## 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

No additional information available

#### Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

#### **SECTION 11: Toxicological information**

I	E	К	Inf	O	rm	at	io	n	0	n i	tox	ic	old	oa	ica	ıl e	eff	e	C	S	

Acute toxicity (oral) Not classified Acute toxicity (dermal) Not classified Acute toxicity (inhalation) Not classified

LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))
butane, liquefied, under pressure (106-97-8)	

LC50 Inhalation - Rat	1442.738 – 1443 mg/l 15 MIN
LC50 Inhalation - Rat [ppm]	800000 ppm 15 MIN

Ethanol (64-17-5)

propane (74-98-6)

Lilianoi (04-17-3)	
LD50 oral rat	10470 mg/kg
LD50 dermal rabbit	> 15800 mg/kg
LC50 Inhalation - Rat	51 mg/l/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation. Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified Carcinogenicity : Not classified : Not classified Reproductive toxicity : Not classified STOT-single exposure : Not classified STOT-repeated exposure

diethyl phthalate (84-66-2)	
NOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat

: Not classified Aspiration hazard

Air Scents fresh dry room spray - Amber & oud					
Vaporizer	Aerosol				

## propane (74-98-6)

Animal studies and expert judgment for classification False

butane, liquefied, under pressure (106-97-8)

Animal studies and expert judgment for classification False

# Ethanol (64-17-5)

Animal studies and expert judgment for classification False

#### diethyl phthalate (84-66-2)

Animal studies and expert judgment for classification False

#### **SECTION 12: Ecological information**

#### 12.1. Toxicity

: Toxic to aquatic life. Harmful to aquatic life with long lasting effects. Ecology - general

6/10 5/28/2026 (Revision date) ZA - en

# Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

Hazardous to the aquatic environment, short-term

(acute)

: Not classified

Hazardous to the aquatic environment, long-term

: Harmful to aquatic life with long lasting effects.

(chronic)

propane (74-98-6)	
LC50 - Fish [1]	24 mg/l (96 h, Pisces, Literature study)
LC50 - Fish [2]	49.9 mg/l (96 h, Pisces, Fresh water, QSAR)
EC50 - Crustacea [1]	7 mg/l (48 h, Daphnia magna, Literature study)
BCF - Fish [1]	9 – 25 (Pisces, QSAR)
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)
butane, liquefied, under pressure (106-97-8	)
LC50 - Fish [1]	1000 mg/l (96 h, Pimephales promelas, QSAR)
EC50 72h - Algae [1]	5.3 – 5.5 mg/l (Algae, QSAR)
Partition coefficient n-octanol/water (Log Pow)	2.89 (Experimental value)
Ethanol (64-17-5)	
LC50 - Fish [1]	11.2 mg/l
EC50 - Crustacea [1]	5012 mg/l
Bioconcentration factor (BCF REACH)	< 10
diethyl phthalate (84-66-2)	
LC50 - Fish [1]	29 mg/l Test organisms (species): Cyprinodon variegatus
LC50 - Fish [2]	12 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 72h - Algae [1]	23 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	45 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	25 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	5 mg/l Test organisms (species): Cyprinus carpio Duration: '28 d'

# 12.2. Persistence and degradability

Air Scents fresh dry room spray - Amber & oud					
Persistence and degradability	No additional information available				
propane (74-98-6)					
Persistence and degradability	Readily biodegradable in water.				
butane, liquefied, under pressure (106-97-8)					
Persistence and degradability	Readily biodegradable in water.				
Ethanol (64-17-5)					
Chemical oxygen demand (COD)	2.04 g O <sub>2</sub> /g substance				

# 12.3. Bioaccumulative potential

Air Scents fresh dry room spray - Amber & oud			
Bioaccumulative potential	No additional information available		

# Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

propane (74-98-6)					
BCF - Fish [1]	9 – 25 (Pisces, QSAR)				
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)				
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).				
butane, liquefied, under pressure (106-97-8)					
Partition coefficient n-octanol/water (Log Pow)	2.89 (Experimental value)				
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).				
Ethanol (64-17-5)					
Bioconcentration factor (BCF REACH)	< 10				

# 12.4. Mobility in soil

Air Scents fresh dry room spray - Amber & oud		
Mobility in soil	No additional information available	
propane (74-98-6)		
Surface tension	0.016 N/m (-47 °C)	
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)	
Ecology - soil	Not applicable (gas).	
butane, liquefied, under pressure (106-97-8)		
Surface tension	< 0.1 N/m (0 °C)	
Partition coefficient n-octanol/water (Log Pow)	2.89 (Experimental value)	
Ecology - soil	Not applicable (gas).	
Ethanol (64-17-5)		
Mobility in soil	1	

#### 12.5. Other adverse effects

Ozone : Not classified

Other adverse effects : No additional information available

# **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

# **SECTION 14: Transport information**

In accordance with SANS / IMDG / IATA

SANS	IMDG	IATA		
14.1. UN number				
1950	1950	1950		
14.2. Proper Shipping Name				
AEROSOLS	AEROSOLS	Aerosols, flammable		
14.3. Transport hazard class(es)				
2.1	2.1	2.1		

#### Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

SANS	IMDG	IATA
2		2
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available	I	1

#### 14.6. Special precautions for user

**SANS** 

Special provisions (SANS) : 63, 190
Limited quantities (SANS) : See SP277
Limited quantities (SANS) : See SP277
Packagings, large packagings and IBCs Packing : P003

instructions (SANS)

Packagings, large packagings and IBCs Special

packing instructions (SANS)

: PP17, PP87

**IMDG** 

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Packing instructions (IMDG) : P207, LP200 Special packing provisions (IMDG) : PP87, L2

EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES

EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)

Stowage category (IMDG): NoneStowage and handling (IMDG): SW1, SW22Segregation (IMDG): SG69

IATA

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

#### **SECTION 15: Regulatory information**

#### 15.1. Safety, health, and environmental national regulations specific for the product

No additional information available

### **SECTION 16: Other information**

Issue date : 28/05/2024 Revision date : 28/05/2026

# Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

Full text of H-statements		
H220	Extremely flammable gas	
H225	Highly flammable liquid and vapour	
H227	Combustible liquid	
H280	Contains gas under pressure; may explode if heated	
H301	Toxic if swallowed	
H302	Harmful if swallowed	
H303	May be harmful if swallowed	
H312	Harmful in contact with skin	
H313	May be harmful in contact with skin	
H315	Causes skin irritation	
H317	May cause an allergic skin reaction	
H318	Causes serious eye damage	
H319	Causes serious eye irritation	
H400	Very toxic to aquatic life	
H401	Toxic to aquatic life	
H402	Harmful to aquatic life	
H410	Very toxic to aquatic life with long lasting effects	
H411	Toxic to aquatic life with long lasting effects	
H412	Harmful to aquatic life with long lasting effects	

Safety Data Sheet (SDS), South Africa

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.