

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010 Issue date: 5/28/2024 Revision date: 5/28/2026 Version: 1.1

SECTION 1: Identification

1.1. Product identifier

Product form Trade name Type of product Product code Product group

: Mixture

- : Air Scents fresh dry room spray Cotton fresh
- : Air freshener
- : SH1289
- : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

:

Use of the substance/mixture

1.3. Supplier's details

Manufacturer

Shield Chemicals (Pty) Ltd 9 London Rd Apex P.O. Box 1939 1501 Benoni – Gauteng South Africa T (011) 421 7111 Contact: Jayson Clark

1.4. Emergency telephone number

Emergency number

: (011) 421 7111

SECTION 2: Hazards identificatio	n	
2.1. Classification of the substance of	r mixture	
Classification according to the United Nat	ions GHS	
Aerosol, Category 1		H222;H229
Serious eye damage/eye irritation, Category	2A	H319
Hazardous to the aquatic environment - Acu	te Hazard, Category 2	H401
Hazardous to the aquatic environment – Chr Full text of H-statements: see section 16	onic Hazard, Category 3	H412
2.2. Label elements		
Hazard pictograms (GHS ZA)		
Signal word (GHS-ZA)	: Danger	
Hazard statements (GHS ZA)	: H222 - Extreme	ely flammable aerosol
		ised container: May burst if heated
		serious eye irritation
	H401 - Toxic to	•
Precautionary statements (GHS ZA)		l to aquatic life with long lasting effects way from heat, hot surfaces, sparks, open flames and other ignition sources.
Frecautionary statements (GH3 ZA)	No smoking.	vay non near, not surfaces, sparks, open names and other ignition sources.
	0	spray on an open flame or other ignition source.
		pierce or burn, even after use.
		elease to the environment.
	P280 - Wear e	ye protection, protective clothing, protective gloves.
	P305+P351+P	338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

	contact lenses, if present and easy to do. Continue rinsing. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 - Dispose of contents and container to a hazardous or special waste collection point.
2.3. Other hazards	
Adverse physicochemical, human health and environmental effects	: Pressurised container: May burst if heated, Extremely flammable aerosol, Causes serious eye irritation, Toxic to aquatic life, Harmful to aquatic life with long lasting effects.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
butane, liquefied, under pressure	CAS-No.: 106-97-8	40.0 - 50.0	Flam. Gas 1, H220 Pyr. Gas Not classified Press. Gas (Liq.), H280 Acute Tox. Not classified (Inhalation:gas)
Ethanol	CAS-No.: 64-17-5	30.0 - 40.0	Flam. Liq. 2, H225 Acute Tox. Not classified (Oral) Acute Tox. Not classified (Dermal) Acute Tox. Not classified (Inhalation:dust,mist) Eye Irrit. 2A, H319 Aquatic Acute Not classified
benzyl benzoate	CAS-No.: 120-51-4	1.0 - 5.0	Acute Tox. 5 (Oral), H303 Acute Tox. 5 (Dermal), H313 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
propane	CAS-No.: 74-98-6	20.0 - 30.0	Flam. Gas 1, H220 Pyr. Gas Not classified Press. Gas (Liq.), H280 Acute Tox. Not classified (Inhalation:gas) Aquatic Acute Not classified

SECTION 4: First aid measures		
4.1. Description of first aid measures	s .	
First-aid measures after inhalation First-aid measures after skin contact First-aid measures after eye contact	 Remove person to fresh air and keep comfortable for breathing. Wash skin with plenty of water. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. 	
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.	
4.2. Most important symptoms and effects, both acute and delayed		
Symptoms/effects after eye contact	: Eye irritation.	
4.3. Indication of any immediate medical attention and special treatment needed		

Treat symptomatically.

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010	
SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
5.2. Special hazards arising from the subs	tance or mixture
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	 Extremely flammable aerosol. Pressurised container: May burst if heated. Toxic fumes may be released.
5.3. Advice for firefighters	
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
SECTION 6: Accidental release measu	ires
6.1. Personal precautions, protective equip	pment and emergency procedures
No additional information available	
6.1.1. For non-emergency personnel	
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	
Avoid release to the environment.	
6.3. Methods and material for containment	and cleaning up
For containment Methods for cleaning up Other information	 Collect spillage. Mechanically recover the product. Dispose of materials or solid residues at an authorized site.
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or

Hygiene measures	 other ignition source. Do not pierce or burn, even after use. Avoid contact with skin and eyes. Wear personal protective equipment. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, including a	ny incompatibilities
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a

well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

propane (74-98-6)		
South Africa - Occupational Exposure Limits (Airborne Pollutants)		
Local name	Propane	
OEL TWA	1800 mg/m ³	
OEL TWA	1000 ppm	
Regulatory reference	Government Notice No. R 904	
butane, liquefied, under pressure (106-97-8)		
South Africa - Occupational Exposure Limits (Airborne Pollutants)		
Local name	n-Butane	
OEL TWA	1430 mg/m ³	
OEL TWA	600 ppm	
OEL STEL	1780 mg/m ³	
OEL STEL	750 ppm	
Regulatory reference	Government Notice No. R 904	

8.2. Appropriate engineering controls

Appropriate engineering controls Environmental exposure controls	Ensure good ventilation of the work station.Avoid release to the environment.

: Protective gloves

: Safety glasses

8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection Eye protection Skin and body protection Respiratory protection

Wear suitable protective clothingIn case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Dhyraiaal atota		المرينط
Physical state	:	Liquid
Appearance	:	Liquid.
Colour	:	clear.
Odour	:	Cotton.
Odour threshold	:	No data available
рН	:	No data available
pH solution	:	No data available
Relative evaporation rate (butylacetate=1)	:	No data available
Relative evaporation rate (ether=1)	:	No data available
Melting point	:	Not applicable
Freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

Flammability Vapour pressure Vapour pressure at 50°C Relative vapour density at 20°C Relative density Relative density of saturated gas/air mixture Density Relative gas density Solubility Partition coefficient n-octanol/water (Log Pow) Partition coefficient n-octanol/water (Log Kow) Viscosity, kinematic Viscosity, dynamic Explosive properties Oxidising properties	 Extremely flammable aerosol. No data available
Explosive properties	: Pressurised container: May burst if heated.
Explosive limits	: No data available : No data available
Lower explosion limit Upper explosion limit	No data availableNo data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects			
Acute toxicity (oral) :	Not classified		
Acute toxicity (dermal) :	: Not classified		
Acute toxicity (inhalation) :	: Not classified		
propane (74-98-6)			
LC50 Inhalation - Rat [ppm] > 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (ga			
butane, liquefied, under pressure (106-97-8)			
LC50 Inhalation - Rat 1442.738 – 1443 mg/l 15 MIN			
LC50 Inhalation - Rat [ppm]	800000 ppm 15 MIN		

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

Ethanol (64-17-5)	
LD50 oral rat	10470 mg/kg
LD50 dermal rabbit	> 15800 mg/kg
LC50 Inhalation - Rat	51 mg/l/4h
benzyl benzoate (120-51-4)	•
LD50 oral rat	> 2000 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2 ml/kg (Modification of Draize 1959 method, 4 h, Rabbit, Experimental value, Dermal)
Skin corrosion/irritation :	Not classified
Serious eye damage/irritation :	Causes serious eye irritation.
Respiratory or skin sensitisation :	Not classified
Germ cell mutagenicity :	Not classified
Carcinogenicity :	Not classified
Reproductive toxicity :	Not classified
STOT-single exposure :	Not classified
STOT-repeated exposure :	Not classified
Aspiration hazard :	Not classified
Air Scents fresh dry room spray - Cotton fres	h
Vaporizer	Aerosol
propane (74-98-6)	
Animal studies and expert judgment for classification	False
butane, liquefied, under pressure (106-97-8)	
Animal studies and expert judgment for classification	False
Ethanol (64-17-5)	
Animal studies and expert judgment for classification	False
benzyl benzoate (120-51-4)	
Animal studies and expert judgment for classification	False

SECTION 12: Ecological information

12.1. Toxicity	
Hazardous to the aquatic environment, short-term : (acute)	Toxic to aquatic life. Harmful to aquatic life with long lasting effects. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.
propane (74-98-6)	
LC50 - Fish [1]	24 mg/l (96 h, Pisces, Literature study)
LC50 - Fish [2]	49.9 mg/l (96 h, Pisces, Fresh water, QSAR)
EC50 - Crustacea [1]	7 mg/l (48 h, Daphnia magna, Literature study)
BCF - Fish [1]	9 – 25 (Pisces, QSAR)
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)
butane, liquefied, under pressure (106-97-8)	
LC50 - Fish [1]	1000 mg/l (96 h, Pimephales promelas, QSAR)
EC50 72h - Algae [1]	5.3 – 5.5 mg/l (Algae, QSAR)

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

butane, liquefied, under pressure (106-97-8)		
Partition coefficient n-octanol/water (Log Pow)	2.89 (Experimental value)	
Ethanol (64-17-5)	·	
LC50 - Fish [1]	11.2 mg/l	
EC50 - Crustacea [1]	5012 mg/l	
Bioconcentration factor (BCF REACH)	< 10	
benzyl benzoate (120-51-4)	·	
LC50 - Fish [1]	2.32 mg/l (EU Method C.1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value, GLP)	
EC50 - Crustacea [1]	3.09 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)	
EC50 72h - Algae [1]	0.475 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)	
BCF - Fish [1]	2.286 (BCFBAF v3.00, Pisces, QSAR)	
Partition coefficient n-octanol/water (Log Pow)	3.97 (Experimental value, 25 °C)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)	

12.2. Persistence and degradability

Air Scents fresh dry room spray - Cotton fresh	
No additional information available	
propane (74-98-6)	
Readily biodegradable in water.	
butane, liquefied, under pressure (106-97-8)	
Readily biodegradable in water.	
Ethanol (64-17-5)	
2.04 g O ₂ /g substance	
benzyl benzoate (120-51-4)	
Readily biodegradable in water.	

12.3. Bioaccumulative potential

Air Scents fresh dry room spray - Cotton fresh		
ioaccumulative potential No additional information available		
propane (74-98-6)		
BCF - Fish [1] 9 – 25 (Pisces, QSAR)		
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
butane, liquefied, under pressure (106-97-8)		
Partition coefficient n-octanol/water (Log Pow)	2.89 (Experimental value)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

Ethanol (64-17-5)		
Bioconcentration factor (BCF REACH)	< 10	
benzyl benzoate (120-51-4)		
BCF - Fish [1]	2.286 (BCFBAF v3.00, Pisces, QSAR)	
Partition coefficient n-octanol/water (Log Pow)	3.97 (Experimental value, 25 °C)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	

12.4. Mobility in soil

Air Scents fresh dry room spray - Cotton fresh		
Mobility in soil	No additional information available	
propane (74-98-6)		
Surface tension	0.016 N/m (-47 °C)	
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)	
Ecology - soil	Not applicable (gas).	
butane, liquefied, under pressure (106-97-8)		
Surface tension	< 0.1 N/m (0 °C)	
Partition coefficient n-octanol/water (Log Pow)	2.89 (Experimental value)	
Ecology - soil	Not applicable (gas).	
Ethanol (64-17-5)		
Mobility in soil	1	
benzyl benzoate (120-51-4)		
Surface tension	0.027 N/m (210 °C)	
Partition coefficient n-octanol/water (Log Pow)	3.97 (Experimental value, 25 °C)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)	
Ecology - soil	Low potential for mobility in soil.	
12.5. Other adverse effects		
Ozone : Other adverse effects :	Not classified No additional information available	

SECTION 13: Disposal considerations
13.1. Disposal methods

Waste treatment methods

: Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with SANS / IMDG / IATA

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

SANS	IMDG	ΙΑΤΑ
14.1. UN number		
1950	1950	1950
14.2. Proper Shipping Name		
AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)		•
2.1	2.1	2.1
	2	
14.4. Packing group		•
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available		
14.6. Special precautions for user		
SANS Special provisions (SANS) Limited quantities (SANS) Limited quantities (SANS) Packagings, large packagings and IBCs Packing instructions (SANS) Packagings, large packagings and IBCs Special packing instructions (SANS) IMDG Special provisions (IMDG) Packing instructions (IMDG) Special packing provisions (IMDG) EmS-No. (Fire) EmS-No. (Spillage) Stowage category (IMDG) Stowage and handling (IMDG)	 63, 190 See SP277 See SP277 P003 PP17, PP87 63, 190, 277, 327, 344, 381, 959 P207, LP200 PP87, L2 F-D - FIRE SCHEDULE Delta - FLAMMABI S-U - SPILLAGE SCHEDULE Uniform - GA None SW1, SW22 	LE GASES ASES (FLAMMABLE, TOXIC OR CORROSIVE)
Segregation (IMDG) IATA PCA Excepted quantities (IATA) PCA Limited quantities (IATA) PCA limited quantity max net quantity (IATA) PCA packing instructions (IATA) PCA max net quantity (IATA) CAO packing instructions (IATA) CAO max net quantity (IATA) Special provisions (IATA) ERG code (IATA)	 : SG69 : E0 : Y203 : 30kgG : 203 : 75kg : 203 : 150kg : A145, A167, A802 : 10L 	

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

SECTION 15: Regulatory information

15.1. Safety, health, and environmental national regulations specific for the product

No additional information available

SECTION 16: Other information

Issue date Revision date : 28/05/2024 : 28/05/2026

Full text of H-statements	
H220	Extremely flammable gas
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H227	Combustible liquid
H280	Contains gas under pressure; may explode if heated
H301	Toxic if swallowed
H303	May be harmful if swallowed
H304	May be fatal if swallowed and enters airways
H313	May be harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), South Africa

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.