

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010 Issue date: 5/28/2024 Revision date: 5/28/2026 Version: 1.1

SECTION 1: Identification	
1.1. Product identifier	
Product form Trade name Type of product Product code Product group	 Mixture Air Scents fresh dry room spray - Wild apple & spice Air freshener SH1288 Trade product
1.2. Relevant identified uses of the substan	nce or mixture and uses advised against
Use of the substance/mixture	:
1.3. Supplier's details	
Manufacturer Shield Chemicals (Pty) Ltd 9 London Rd Apex P.O. Box 1939 1501 Benoni – Gauteng South Africa T (011) 421 7111 Contact: Jayson Clark	
1.4. Emergency telephone number	
Emergency number	: (011) 421 7111
SECTION 2: Hazards identification 2.1. Classification of the substance or mixt	ure
Classification according to the United Nations G Aerosol, Category 1 Serious eye damage/eye irritation, Category 2A Hazardous to the aquatic environment – Acute Haza Full text of H-statements: see section 16	H222;H229 H319
2.2. Label elements	
Labelling according to the United Nations GHS Hazard pictograms (GHS ZA)	
Signal word (GHS-ZA) Hazard statements (GHS ZA)	 Danger H222 - Extremely flammable aerosol H229 - Pressurised container: May burst if heated H319 - Causes serious eye irritation H402 - Harmful to aquatic life
Precautionary statements (GHS ZA)	 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P273 - Avoid release to the environment. P280 - Wear eye protection, protective clothing, protective gloves. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

	contact lenses, if present and easy to do. Continue rinsing. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 - Dispose of contents and container to a hazardous or special waste collection point.
2.3. Other hazards	
Adverse physicochemical, human health and environmental effects	: Pressurised container: May burst if heated, Extremely flammable aerosol, Causes serious eye irritation, Toxic to aquatic life

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
butane, liquefied, under pressure	CAS-No.: 106-97-8	40.0 - 50.0	Flam. Gas 1, H220 Pyr. Gas Not classified Press. Gas (Liq.), H280 Acute Tox. Not classified (Inhalation:gas)
Ethanol	CAS-No.: 64-17-5	30.0 - 40.0	Flam. Liq. 2, H225 Acute Tox. Not classified (Oral) Acute Tox. Not classified (Dermal) Acute Tox. Not classified (Inhalation:dust,mist) Eye Irrit. 2A, H319 Aquatic Acute Not classified
propane	CAS-No.: 74-98-6	20.0 - 30.0	Flam. Gas 1, H220 Pyr. Gas Not classified Press. Gas (Liq.), H280 Acute Tox. Not classified (Inhalation:gas) Aquatic Acute Not classified

SECTION 4: First aid measures 4.1. Description of first aid measures First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. First-aid measures after skin contact : Wash skin with plenty of water. First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell. 4.2. Most important symptoms and effects, both acute and delayed Symptoms/effects after eye contact Symptoms/effects after eye contact : Eye irritation. 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

5.2. Special hazards arising from the substa	ance or mixture
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	 Extremely flammable aerosol. Pressurised container: May burst if heated. Toxic fumes may be released.
5.3. Advice for firefighters	
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release r	neasures
6.1. Personal precautions, protectiv	e equipment and emergency procedures
No additional information available	
6.1.1. For non-emergency personnel	
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	
Avoid release to the environment.	
6.3. Methods and material for contain	inment and cleaning up
For containment Methods for cleaning up Other information	 Collect spillage. Mechanically recover the product. Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Precautions for safe handling Hygiene measures	 Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin and eyes. Wear personal protective equipment. Do not eat, drink or smoke when using this product. Always wash hands after handling the 	
7.2. Conditions for safe storage, in	product.	
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a	

well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

propane (74-98-6)		
South Africa - Occupational Exposure Limits (Airborne Pollutants)		
Local name	Propane	
OEL TWA	1800 mg/m ³	
OEL TWA	1000 ppm	

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

propane (74-98-6)		
Regulatory reference	Government Notice No. R 904	
butane, liquefied, under pressure (106-97-8)		
South Africa - Occupational Exposure Limits (Airborne Pollutants)		
Local name	n-Butane	
OEL TWA	1430 mg/m ³	
OEL TWA	600 ppm	
OEL STEL	1780 mg/m ³	
OEL STEL	750 ppm	
Regulatory reference	Government Notice No. R 904	

8.2. Appropriate engineering controls

Appropriate engineering controls Environmental exposure controls Ensure good ventilation of the work station.Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection	:	Protective gloves
Eye protection	:	Safety glasses
Skin and body protection	:	Wear suitable protective clothing
Respiratory protection	:	In case of insufficient ventilation, wear suitable respiratory equipment
Personal protective equipment symbol(s):		

8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties Physical state

Flysical state	. Liquiu
Appearance	: Liquid.
Colour	: clear.
Odour	: Apple. Spice.
Odour threshold	: No data available
рН	: No data available
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability	: Extremely flammable aerosol.
Vapour pressure	: No data available
Vapour pressure at 50°C	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Relative density of saturated gas/air mixture	: No data available

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

Density Relative gas density Solubility Partition coefficient n-octanol/water (Log Pow) Partition coefficient n-octanol/water (Log Kow) Viscosity, kinematic Viscosity, kinematic Viscosity, dynamic Explosive properties Oxidising properties Explosive limits	 No data available Pressurised container: May burst if heated. No data available
Upper explosion limit	: No data available

9.2. Other information

No

No additional information available
SECTION 10: Stability and reactivity
10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information				
11.1. Information on toxicological effects				
Acute toxicity (dermal)	Not classified Not classified Not classified			
propane (74-98-6)				
LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))			
butane, liquefied, under pressure (106-97-8)				
LC50 Inhalation - Rat	1442.738 – 1443 mg/l 15 MIN			
LC50 Inhalation - Rat [ppm]	800000 ppm 15 MIN			
Ethanol (64-17-5)				
LD50 oral rat	10470 mg/kg			
LD50 dermal rabbit	> 15800 mg/kg			
LC50 Inhalation - Rat	51 mg/l/4h			

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

: Not classified		
: Causes serious eye irritation.		
: Not classified		
Air Scents fresh dry room spray - Wild apple & spice		
Aerosol		
propane (74-98-6)		
cation False		
butane, liquefied, under pressure (106-97-8)		
cation False		
Ethanol (64-17-5)		
cation False		

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Hazardous to the aquatic environment, short-term : (acute) Hazardous to the aquatic environment, long-term :	Toxic to aquatic life. Harmful to aquatic life. Not classified	
(chronic)		
propane (74-98-6)		
LC50 - Fish [1]	24 mg/l (96 h, Pisces, Literature study)	
LC50 - Fish [2]	49.9 mg/l (96 h, Pisces, Fresh water, QSAR)	
EC50 - Crustacea [1]	7 mg/l (48 h, Daphnia magna, Literature study)	
BCF - Fish [1]	9 – 25 (Pisces, QSAR)	
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)	
butane, liquefied, under pressure (106-97-8)		
LC50 - Fish [1]	1000 mg/l (96 h, Pimephales promelas, QSAR)	
EC50 72h - Algae [1]	5.3 – 5.5 mg/l (Algae, QSAR)	
Partition coefficient n-octanol/water (Log Pow)	2.89 (Experimental value)	
Ethanol (64-17-5)		
LC50 - Fish [1]	11.2 mg/l	
EC50 - Crustacea [1]	5012 mg/l	
Bioconcentration factor (BCF REACH)	< 10	
12.2. Persistence and degradability		
Air Scents fresh dry room spray - Wild apple & spice		
Persistence and degradability	No additional information available	

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

propane (74-98-6)			
Persistence and degradability	Readily biodegradable in water.		
butane, liquefied, under pressure (106-97-8)	butane, liquefied, under pressure (106-97-8)		
Persistence and degradability	Readily biodegradable in water.		
Ethanol (64-17-5)			
Chemical oxygen demand (COD)	2.04 g O ₂ /g substance		
12.3. Bioaccumulative potential			
Air Scents fresh dry room spray - Wild apple	e & spice		
Bioaccumulative potential	No additional information available		
propane (74-98-6)			
BCF - Fish [1]	9 – 25 (Pisces, QSAR)		
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)		
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).		
butane, liquefied, under pressure (106-97-8)			
Partition coefficient n-octanol/water (Log Pow)	2.89 (Experimental value)		
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).		
Ethanol (64-17-5)			
Bioconcentration factor (BCF REACH)	< 10		
12.4. Mobility in soil			
Air Scents fresh dry room spray - Wild apple	e & spice		
Mobility in soil	No additional information available		
propane (74-98-6)	·		
Surface tension	0.016 N/m (-47 °C)		
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)		
Ecology - soil	Not applicable (gas).		
butane, liquefied, under pressure (106-97-8)			
Surface tension	< 0.1 N/m (0 °C)		
Partition coefficient n-octanol/water (Log Pow)	2.89 (Experimental value)		
Ecology - soil	Not applicable (gas).		
Ethanol (64-17-5)			
Mobility in soil	1		
12.5. Other adverse effects			
Ozone Other adverse effects	: Not classified : No additional information available		

SECTION 13: Disposal considerations	
13.1. Disposal methods	

Waste treatment methods

: Dispose of contents/container in accordance with licensed collector's sorting instructions.

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

SECTION 14: Transport information		
In accordance with SANS / IMDG / IATA		
SANS	IMDG	ΙΑΤΑ
14.1. UN number		
1950	1950	1950
14.2. Proper Shipping Name		
AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)		· · ·
2.1	2.1	2.1
	2	
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available		1
14.6. Special precautions for user		
SANS Special provisions (SANS) Limited quantities (SANS) Limited quantities (SANS) Packagings, large packagings and IBCs Packing instructions (SANS) Packagings, large packagings and IBCs Special packing instructions (SANS) IMDG Special provisions (IMDG) Packing instructions (IMDG) Special packing provisions (IMDG) EmS-No. (Fire) EmS-No. (Spillage) Stowage category (IMDG) Stowage and handling (IMDG) Segregation (IMDG)	 : 63, 190 : See SP277 : See SP277 : P003 : PP17, PP87 : 63, 190, 277, 327, 344, 381, 959 : P207, LP200 : P207, LP200 : PP87, L2 : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE) : None : SW1, SW22 : SG69	
IATA PCA Excepted quantities (IATA) PCA Limited quantities (IATA) PCA limited quantity max net quantity (IATA) PCA packing instructions (IATA) PCA max net quantity (IATA) CAO packing instructions (IATA) CAO max net quantity (IATA) Special provisions (IATA) ERG code (IATA)	 E0 Y203 30kgG 203 75kg 203 150kg A145, A167, A802 10L 	

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

SECTION 15: Regulatory information

15.1. Safety, health, and environmental national regulations specific for the product

No additional information available

SECTION 16: Other information

Issue date Revision date : 28/05/2024 : 28/05/2026

Full text of H-statements		
H220	Extremely flammable gas	
H225	Highly flammable liquid and vapour	
H226	Flammable liquid and vapour	
H227	Combustible liquid	
H280	Contains gas under pressure; may explode if heated	
H301	Toxic if swallowed	
H302	Harmful if swallowed	
H303	May be harmful if swallowed	
H311	Toxic in contact with skin	
H313	May be harmful in contact with skin	
H315	Causes skin irritation	
H317	May cause an allergic skin reaction	
H319	Causes serious eye irritation	
H400	Very toxic to aquatic life	
H401	Toxic to aquatic life	
H402	Harmful to aquatic life	
H412	Harmful to aquatic life with long lasting effects	

Safety Data Sheet (SDS), South Africa

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.